

Overview

HPE Alletra 6000

Experience the Power of Predictive

Is your enterprise class storage holding you back because you are tied down administering, tuning, and supporting infrastructure? Are you looking to shift to a cloud everywhere experience with the same agility, simplicity, and cloud consumption for every application?

HPE Alletra powers your data from edge-to-core with the cloud experience for all your apps. For business-critical workloads, HPE Alletra 6000 delivers fast, consistent performance and industry leading data efficiency. It enables IT to shift from owning and maintaining data infrastructure to simply accessing and utilizing it on-demand, as-a-service. Eliminate performance and efficiency trade-offs with no knobs or configurations to adjust and always-on data services. Get resilient storage with intelligence and a no single point of failure platform that together deliver 6-nines availability guaranteed. Deliver on recovery SLAs with fast, integrated app aware backup and recovery—on-premises and in the cloud.

What's new

- Eliminate complexity by unifying infrastructure management silos under a cloud managed single pane of glass - accessible from anywhere and from any device.
- Developed from the foundation of HPE Nimble Storage architecture, proven to deliver speed, efficient, and resiliency with cloud agility.
- Delivers up to 3X faster performance than previous HPE Nimble Storage All Flash Arrays.
- Designed for high availability requirements with 6-nines availability guaranteed as a standard benefit without requiring a special contract.
- HPE Store More Guarantee¹ delivers more effective capacity per terabyte of raw flash than competitive all-flash arrays.
- Eliminate forklift upgrades, non-disruptive controller upgrades, flat support pricing, and flexible consumption options.

Notes:

- For more information about HPE Alletra, go to: <https://www.hpe.com/storage/Alletra>
- ¹For details on the HPE 6-Nines Guarantee, refer to: <https://www.hpe.com/psnow/doc/a50003574enw>

Overview



HPE Alletra 6000 array
(Base array, 4U; 24 bays with NVMe SSDs)



Standard Features

AI-driven

- Predict and prevent disruptions across storage, services, and virtual machines, resulting in savings of over 1.5 million hours of lost productivity due to downtime.
 - Redefine support experience with predictive support automation that delivers an unprecedented support experience with automated L1 and L2 and direct access to the resources you need.
 - Pinpoint issues between storage and VMs and underutilized virtual resources without effort.
 - Take the guesswork out of managing data infrastructure with AI-driven recommendations that improves performance, drives higher availability, and optimizes resource utilization and planning.
-

Built for Cloud

- Setup in minutes because systems are automatically discovered, on-boarded, and configured.
 - Say goodbye to time-consuming, LUN-centric provisioning with AI-driven, intent based provisioning of application workloads on infrastructure best suited for optimizing SLAs.
 - Experience faster access to innovation with no disruptions because new features and enhancements are instantly available through self-service upgrades.
 - Manage from anywhere with simple global management driven through a SaaS-based user experience.
-

As-a-Service

- Consume data infrastructure as a service via HPE GreenLake, eliminating up front capital costs with a pay-per-use model.
 - Shift from owning and maintaining data infrastructure to simple accessing and utilizing it on-demand.
 - Free up your cash flow and increase financial agility with the right mix of subscription and consumption-based services.
-

Absolute Resiliency

- 99.9999% (6-nines) guaranteed availability
 - Triple+ Parity RAID tolerates 3 simultaneous drive failures plus additional protection through intra-drive parity.
 - App-granular, FIPS-certified encryption provides data at rest and over-the-wire protection. Secure data shredding is built in.
 - Native application-consistent snapshots and replication plus integration with leading backup software.
 - Redundant, hot-swap components including controllers, power supplies, SSDs, and IO cards.
-

HPE Data Services

HPE Alletra 6000 arrays include a subscription to HPE Data Ops Manager for cloud-based management of the array from the HPE Data Services. The subscription is included in the quote when support is selected and has the same duration as support. For more information, please refer to the HPE Data Services QuickSpecs:

<https://h20195.www2.hpe.com/v2/getdocument.aspx?docname=a50002569enw>



Standard Features

HPE Alletra 6000 Models						
AF-Series Arrays	6010	6030	6050	6070	6090	Scale-out ¹ 4X 6090
Raw capacity (TB) ^{2,5}	23-92	23-184	23-575	23-1,104	23-1,104	92-4,416
Usable capacity (TB) ^{2,8}	12-66	12-135	12-422	12-820	12-820	48-3,260
Effective capacity (TB) ^{2,3}	60-330	60-675	60-2,110	60-4,100	60-4,100	240-16,400
Max. # of expansion shelves	1	2	2	2	2	8
RAID level support	Triple+ Parity					
Onboard Mgmt 1GBase-T ports per array ^{4,6}	8	8	8	8	8	32
Optional iSCSI 10GBase-T ports per array ⁶	8-24	8-48	8-48	8-48	8-48	8-192
Optional iSCSI 10GbE ports per array ⁶	8-24	8-48	8-48	8-48	8-48	8-192
Optional iSCSI 25GbE ports per array ⁶	4-12	4-24	4-24	4-24	4-24	4-96
Optional iSCSI 100GbE ports per array ⁶	4	4, 8	4, 8	4, 8	4, 8	4-48
Optional 2P 32Gb FC (8/16Gb) ports per array ^{6,9}	4-12	4-24	4-24	4-24	4-24	4-96
Optional 4P 32Gb FC (8/16Gb) ports per array ^{6,9}	8	8, 16	8, 16	8, 16	8, 16	8-64

Notes:

- Specifications are subject to change without notice.
 - ¹ Scale-out configuration consists of up to four (4) HPE Alletra 6000 and/or Nimble Storage arrays; mixed models and generations supported; specifications listed above are for 4x 6090 arrays, each with two all-flash shelves.
 - ² Raw, usable, and effective capacities are shown in TB (10¹² bytes). Usable and effective capacities take into account space used for parity, spares, and system overhead.
 - ³ Effective capacity is the capacity of the base array and maximum number of expansion shelves. Assumes data reduction of five to one (5:1) from deduplication and compression.
 - ⁴ Each array controller has 4 x 1GbaseT ports built in. Optional ports are 10GbaseT, 10GbE SFP+, 25GbE SFP28, 100GbE QSFP28, and 32Gb (16Gb) FC.
 - ⁵ The Total Max Raw Capacity per system is limited by the architecture of the system and is not to be exceeded, even if it may be possible to configure a system that exceeds this limit.
 - ⁶ Array port counts shown include both controllers.
 - ⁸ Usable capacity has changed from previous generation arrays to allow larger core dumps to be processed on the Alletra 6000. Reference NinjaSTARS for detailed usable capacity.
 - ⁹ The 32Gb Fibre Channel cards can auto-negotiate to 32Gb, 16Gb, or 8Gb connectivity to the switch

Host OS Support

Microsoft® Windows® Server, including Microsoft® Hyper-V™ | VMware vSphere™ | HP-UX® | Ubuntu
 SUSE® Linux Enterprise | SUSE® Linux Virtualization | Red Hat® Enterprise Linux® | Red Hat® Enterprise Virtualization
 CentOS | Oracle® Linux® (UEK and RHEL compatible kernels) | Oracle® Solaris | Citrix® XenServer | IBM® AIX®

Notes: For the latest information on supported operating systems refer to Single Point of Connectivity Knowledge (SPOCK) for HPE Storage products: <https://h20272.www2.hpe.com/spock/>



Service and Support

Warranty

HPE Alletra 6000 arrays come with the following warranties:

- 1-year; parts-only warranty for hardware components, including SSDs
- 90-day, software updates for defects

Additionally, HPE Alletra 6000 will provide phone support for replacing a defective part. Additional support coverage is required for HPE Alletra 6000 arrays.

Notes:

- For hardware warranty claims, defective part must be received before replacement parts are shipped.
- Warranty is provided by HPE Alletra 6000.
- Link to [HPE Global Limited Warranty and Technical Support](#).

Service and Support

Support is required for all HPE Alletra 6000 arrays. Support SKUs provide up to five years of 24x7 telephone and email support for the arrays and hardware components (Including SSDs reaching the write wear limit) with a choice of Next Business Day (NBD) parts exchange, Next Business Day (NBD) onsite support, 4-hour parts exchange, or 4-hour onsite support, access to the HPE InfoSight predictive analytics platform and software updates.

HPE Pointnext **Tech Care** is the new operational service experience for HPE products. Tech Care goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Pointnext Tech Care has been reimaged from the ground up to support a customer-centric, AI-driven, and digitally enabled customer experience to move your business forward.

Notes: Support contract is mandatory for all HPE Alletra 6000 products.

Data Services Support with HPE Alletra 6000

A valid subscription enables the following enterprise-level support:

- 24x7 telephone and email support for all entitled services available through HPE Data Services
- Direct connection to expert-level support within minutes
- Guidance through troubleshooting and configuration of available service and interoperability within your cloud and/or on-premises environment.

Installation Services

Installation Services are intended to guide you from start to finish and to help make your installation a success. Our engagement includes:

- Inventory and verify HPE Alletra 6000 equipment against the sales order
- Physically rack and cable all HPE Alletra 6000 equipment, including connecting network cables provided by the customer
- Conduct power-on tests and verify operation
- Add the array to an existing HPE Alletra 6000 or HPE Nimble Storage Group, if applicable
- Configure array's basic management, monitoring, & reporting capabilities
- Configure array for additional data networks / SAN connectivity as needed
- Upgrade the array to the latest recommended HPE Alletra 6000 or HPE Nimble OS version as needed

HPE Tier 1 Storage Array Startup service - HA124A1#5MR

Provides full hardware and software installation of a new HPE Tier 1 Storage array in a data center with up to six (6) shelves. Quote this service when you want onsite and remote assistance in setting up a new array from hardware racking through setting up vVols on servers in the configuration. This service may not be quoted as part of a Greenfield or Brownfield dHCI storage configuration. [HPE Tier 1 Storage Array Startup Service data sheet](#)



Service and Support

HPE Tier 1 Storage Upgrade service – HA124A1#5MS

On-site installation of upgrades kits or for an existing HPE Tier 1 Storage array. This service is for in-family upgrades only and cannot be quoted to upgrade an existing array to the next generation of storage. This service can be used to upgrade components within an existing Greenfield or Brownfield dHCI storage configuration.

HPE Tier 1 Storage Cross Family Offline Upgrade service – HA124A1#V0R

Provides the on-site hardware upgrade and disk migration from your existing array to the new family array chassis. This service is completed with the array powered off during a downtime window.

Notes: All Installation and upgrade services are optional for all HPE Alletra 6000 products.

Additional Services Available

Get the most from your HPE products. Get the expertise you need at every step of your IT journey with **HPE Pointnext Services**. We help you lower your risks and overall costs using automation and methodologies that have been tested and refined by HPE experts through thousands of deployments globally. HPE Pointnext **Advisory Services** focus on your business outcomes and goals, partnering with you to design your transformation and build a roadmap tuned to your unique challenges. Our **Professional** and **Operational Services** can be leveraged to speed up time-to-production, boost performance and accelerate your business. HPE Pointnext specializes in flawless and on-time implementation, on-budget execution, and creative configurations that get the most out of software and hardware alike.

Consume IT on your terms

HPE GreenLake brings the cloud experience directly to your apps and data wherever they are—the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake accelerates digital transformation in a distributed, edge-to-cloud world.

- Get faster time to market
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

Recommended Services

HPE Pointnext Tech Care.

HPE Pointnext Tech Care is the new operational service experience for HPE products. Tech Care goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Pointnext Tech Care has been reimagined from the ground up to support a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Pointnext Tech Care is available with four service level options for HPE Alletra 6000: . Basic, which provides next business day onsite parts exchange, Basic Exchange which provides next business day parts delivery, Essential which provides 24x7 onsite parts exchange, and Essential Exchange, which provides 24x7 parts delivery. Regardless of the service level, Customers have direct access to Level 3 HPE Alletra 6000 support engineers by telephone 24x7.

For more information: <https://www.hpe.com/services/techcare>



Service and Support

HPE Pointnext Complete Care

HPE Pointnext Complete Care is a modular, edge-to-cloud IT environment service that provides a holistic approach to optimizing your entire IT environment and achieving agreed upon IT outcomes and business goals through a personalized and customer-centric experience. All delivered by an assigned team of HPE Pointnext Services experts. HPE Pointnext Complete Care provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI Driven customer experience

<https://www.hpe.com/services/complecare>

HPE Tier 1 Storage Peer Persistence Setup Service - HA124A1#V0S

Provides remote implementation of the Peer Persistence software functionality available in the HPE Alletra 6000/Nimble Storage operating system (OS). This service provides analysis, implementation, and testing services necessary for you to deploy the HPE Nimble Storage Peer Persistence features.

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Defective media retention(DMR) service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

Comprehensive Defective Material Retention (CDMR) HPE CDMR allows you to keep all data retentive components.

For more information

- <http://www.hpe.com/services>
- <https://www.hpe.com/us/en/services/operational.html>

To learn more on HPE Storage Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE"

<https://www.hpe.com/us/en/contact-hpe.html>

HPE Support Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.

Customers purchasing from a commercial reseller can find HPE Support Services at <https://ssc.hpe.com/portal/site/ssc/>



Configuration Information

Step 1 – Choose Base configuration

All HPE Alletra 6000 come in a 4U form-factor chassis with

- (2) controllers with processors, memory, fans and NVDIMM, and
- (8) 1GBase-T network ports, i.e. (4) per controller for iSCSI or management traffic, and
- All-inclusive software including HPE InfoSight predictive analytics

Additional host connectivity per controller is indicated in the product descriptions below.

Flash capacity upgrades, network upgrades and expansion shelves will be available for integration in the field.

HPE Alletra 6000 – Base Configuration Base Array

Description	SKU
HPE Alletra 6010 Dual Controller Configure-to-order Base Array	R4U28A
HPE Alletra 6030 Dual Controller Configure-to-order Base Array	R4U29A
HPE Alletra 6050 Dual Controller Configure-to-order Base Array	R4U30A
HPE Alletra 6070 Dual Controller Configure-to-order Base Array	R4U31A
HPE Alletra 6090 Dual Controller Configure-to-order Base Array	R4U32A

Step 2 – Choose Power Supplies

All HPE Alletra 6000 require one (1) of the Power Supply Kits listed below. Each Power Supply Kit includes four (4) Power Supplies; either 800W AC, 1600W AC, or 2200W AC.

Table below shows All Flash Array compatibilities with Power Supply Kits.

6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	No	No	HPE Alletra 6000 4x 800W FIO AC Power Supply Kit	R7G12A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 4x 1600W FIO AC Power Supply Kit	R7G13A
Yes	No	No	No	No	HPE Alletra 6000 4x 800W Titanium FIO Power Supply Kit	S0R22A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 2200W Titanium Tech Refresh Power Supply	S0R23A

Notes:

- The R7G12A power supplies support both low-line and high-line
- The R7G13A, S0R22A, S0R23A power supplies support high-line; no low-line support
- The R7G13A power supplies are recommended when there is a choice between R7G12A and R7G13A
- Both the R7G12A and the R7G13A AC power supplies are 80 PLUS Platinum certified
- Both the S0R22A and the S0R23A AC power supplies are 80 PLUS Titanium certified
- The Titanium certified power supply kits (S0R22A & S0R23A) are mandatory to meet EU Lot9 requirements



Configuration Information

Step 3 – Choose Head SSD Capacity

All HPE Alletra 6000 require one or two of the following SSD capacity options.

Table below shows All Flash Array compatibilities with SSD Options.

Head SSD Capacity Options						
6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 23TB (12x1.92TB) NVMe Flash Carrier FIO Flash Bundle	R7S81A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 46TB (12x3.84TB) NVMe Flash Carrier FIO Flash Bundle	R7S83A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 92TB (12x7.68TB) NVMe Flash Carrier FIO Flash Bundle	R7S85A
No	No	Yes	Yes	Yes	HPE Alletra 6000 184TB (12x15.36TB) NVMe Flash Carrier FIO Flash Bundle	R7S87A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 46TB (24x1.92TB) NVMe Flash Carrier FIO Flash Bundle	R7S82A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 92TB (24x3.84TB) NVMe Flash Carrier FIO Flash Bundle	R7S84A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 184TB (24x7.68TB) NVMe Flash Carrier FIO Flash Bundle	R7S86A
No	No	Yes	Yes	Yes	HPE Alletra 6000 368TB (24x15.36TB) NVMe Flash Carrier FIO Flash Bundle	R7S88A

Platform SSD Capacities					
	6010	6030	6050	6070	6090
Minimum platform SSD capacity (RAW)	23 TB	23 TB	23 TB	23 TB	23 TB
Maximum platform SSD capacity (RAW)= (Head SSD+ expansion) capacity (TB)	92 TB	184 TB	575 TB	1104 TB	1104 TB
Memory installed (GB) per controller	64 GB	128 GB	256 GB	448 GB	896 GB

Step 4 – Choose Head Networking Option

Up to six (6) of the following networking options can be selected. Please refer to configuration guidelines for specific support of networking options for each array. The HPE Alletra 6010 array supports up to three (3) head networking options.

Notes:

- The following minimum ports are recommended for best performance:
 - o 6010: at least 2-ports
 - o 6030: at least 4-ports
 - o 6050: at least 8-ports
 - o 6070: at least 8-ports
 - o 6090: at least 8-ports
- Max One (1) Storage Class Memory kit (ROP46B or ROP48B) per 6050/6070/6090 array
- Max Two (2) 100GbE kits or 32Gb FC 4-port kits (ROR18A/ROR19A or ROR14A/ROR15A) per 6030/6050/6070/6090 array
- Max One (1) 100GbE kits or 32Gb FC 4-port kits (ROR18A/ROR19A or ROR14A/ROR15A) per 6010 array
- All 10GbE kits (Q8C17C and Q8C20C) and 32Gb FC kits (ROP34A and ROR14A) include transceivers
- The 10/25GbE Adapter Kit (ROR12A) and the 100GbE Adapter kit (ROR18A) do not include transceivers. If transceivers are required, they will need to be ordered separately.
- Each Head networking option includes two (2x) cards which are evenly populated in the two controllers.



Configuration Information

Head Networking Options						
6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10GbE 4-port FIO Adapter Kit	Q8C17C
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10GBASE-T 4-port FIO Adapter Kit	Q8C20C
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10/25GbE 2-port FIO Adapter Kit	R0R12A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x100GbE 2-port FIO Adapter Kit	R0R18A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x32Gb 2-port Fibre Channel FIO Adapter Kit	R0P34A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x32Gb 4-port Fibre Channel FIO Adapter Kit	R0R14A
No	No	Yes	Yes	Yes	HPE Alletra 6000 1.5TB Storage Class Memory FIO Adapter Kit	R0P46B
Transceivers (FIO)					SKU Description	SKU
Supported with 2x10/25GbE 2-port kits					HPE Alletra 6000 2x10Gb SFP+ SR FIO Transceiver	R7D05A
Supported with 2x10/25GbE 2-port kits					HPE Alletra 6000 2x25Gb SFP28 SR 100m FIO Transceiver	R7D07A
Supported with 2x100GbE 2-port kits					HPE Alletra 6000 2x100Gb QSFP28 MPO SR4 100m FIO Transceiver	R7D08A

Step 5 – Add Software (Mandatory)

HPE Alletra Software and Support SaaS

HPE Alletra 6000 arrays include a subscription to HPE Alletra Software and Support SaaS that enables cloud-based management of the array from the HPE Data Services Cloud Console and access to data services as they become available on HPE GreenLake. The subscription includes access to the HPE Alletra software and related support. It is included in the quote when support is selected and has the same duration as support. For more information, please refer to the HPE Data Services QuickSpecs:

<https://h20195.www2.hpe.com/v2/getdocument.aspx?docname=a50002569enw>.

Description

HPE Alletra 6000 Software and Support SaaS– 1-year Subscription

SKU

S1E76AAE#CTE

Notes: SKU (R7N52AAE#CTE) is only available in Japan.

HPE Alletra 6000 Software and Support SaaS– 3-year Subscription

S1E76AAE#CTF

HPE Alletra 6000 Software and Support SaaS– 4-year Subscription

S1E76AAE#CTG

HPE Alletra 6000 Software and Support SaaS– 5-year Subscription

S1E76AAE#CTH

Subscribe to the HPE Backup and Recovery Service

The HPE Backup and Recovery Service is an optional subscription service available from the HPE GreenLake Cloud Portal. It is the modern way to protect VMware virtual machines that use storage from HPE Alletra systems. The subscription enables automated, Array Optimized, cloud managed protection of the virtual machine. The HPE Backup and Recovery Service is available with a subscription to meet your needs. Working with your HPE account representative you can define whether you want total flexibility to pay for the service as you use it or if you want to lock in lower prices by reserving the service for 1, 2, 3, 4 or 5 years. When you reserve the service you choose the number of virtual machines you want to protect and, if you want to protect your virtual machines with backup to the cloud, the capacity of the Cloud Protection Store you will need. For more information, please refer to the HPE Backup and Recovery Service QuickSpecs:

<https://www.hpe.com/h20195/v2/GetDocument.aspx?docname=a50004269enw>



Configuration Information

Step 6 – Optional NVMe All-Flash Shelf

The HPE Alletra 2140 4U All Flash expansion shelves include two (2) 100Gb QSFP28 to QSFP28 1m direct attach copper (DAC) cables for connectivity. The All Flash expansion shelf requires:

- Min 1/Max 1 of 2x100GbE 2-port OCP Mezzanine adapter kit. Order R6J21A to have the OCP adapters factory integrated into the array when the both the array and expansion shelf are ordered together. Order R6J22A when the expansion shelf is going to be added to an existing array.
- Min 1/Max 1 of the listed Flash Bundles
- Four (4) power supplies
- Four (4) power cords
- With array OS 6.1.2.0 and later, a 2140 expansion shelf can be used with HPE Alletra 6000 configured with 2x 12-SSD flash bundles.

Min 0, Max 2 expansion shelves per array

6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	HPE Alletra 2140 4U All Flash Configure-to-order Expansion Shelf	R6F54A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x100GbE 2-port OCP FIO Mezzanine Adapter Kit	R6J21A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x100GbE 2-port OCP Mezzanine Adapter Field Upgrade	R6J22A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 46TB (24x1.92TB) NVMe Flash Carrier FIO Flash Bundle	R7S82A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 92TB (24x3.84TB) NVMe Flash Carrier FIO Flash Bundle	R7S84A
No	No	Yes	Yes	Yes	HPE Alletra 6000 184TB (24x7.68TB) NVMe Flash Carrier FIO Flash Bundle	R7S86A

6010	6030	6050	6070	6090	SKU Description	SKU
No	No	Yes	Yes	Yes	HPE Alletra 6000 368TB (24x15.36TB) NVMe Flash Carrier FIO Flash Bundle	R7S88A
1	2	2	2	2	Max number of expansion shelves per array model	

Step 7 – Add Support (Mandatory)

Support recommendations are designed to help you enhance technology operations, lower risk, and make it easier for you to seek the right balance between affordability and service-level commitments. Depending on your individual support needs, choose from four levels of Tech Care that cover the entire lifecycle to better address your needs from 3, 4 and 5-year durations for service levels ranging from Basic Exchange (Next Business Day parts exchange) to Essential (4-hour onsite response).

Description

Description	SKU
HPE Tech Care Basic Exchange SVC	HU4B5A3/4/5
HPE Tech Care Basic Exchange w/DMR SVC	HU4B6A3/4/5
HPE Tech Care Basic Exchange w/CDMR SVC	HU4B7A3/4/5
HPE Tech Care Basic SVC	HU4B2A3/4/5
HPE Tech Care Basic w/DMR SVC	HU4B3A3/4/5
HPE Tech Care Basic w/CDMR SVC	HU4B4A3/4/5
HPE Tech Care Essential Exchange SVC	HU4A9A3/4/5
HPE Tech Care Essential Exchange w/DMR SVC	HU4B0A3/4/5

Configuration Information

Description

	SKU
HPE Tech Care Essential Exchange w/CDMR SVC	HU4B1A3/4/5
HPE Tech Care Essential SVC	HU4A6A3/4/5
HPE Tech Care Essential w/DMR SVC	HU4A7A3/4/5
HPE Tech Care Essential w/CDMR SVC	HU4A8A3/4/5

Notes: Minimum support required [3-year HPE Tech Care Basic Exchange](#)

Installation Services

- Installation Services are intended to guide you from start to finish and to help make your installation a success.

Notes: Installation services are optional.

HPE Tier 1 Storage Array Startup service	HA124A1#5MR
HPE Tier 1 Storage Array Upgrade service	HA124A1#5MS
HPE Tier 1 Storage Cross Family Offline Upgrade service	HA124A1#VOR

Racks

HPE Alletra 6000 arrays and expansion shelves are compatible with industry standard 4-post EIA 19-inch racks with square mounting holes, including HPE 36U, 42U and 48U Enterprise Shock Racks. HPE recommends HPE racks with a depth of 1200mm as it provides ample room for cabling and ease of serviceability.

Recommended Racks:

HPE G2 Enterprise Series Racks

- HPE 48U 600mmx1200mm G2 Enterprise Rack
- HPE 48U 800mmx1200mm G2 Enterprise Rack
- HPE 42U 600mmx1200mm G2 Enterprise Rack
- HPE 42U 800mmx1200mm G2 Enterprise Rack

HPE G2 Advanced Series Racks

- HPE 48U 600mmx1200mm G2 Advanced Rack
- HPE 48U 800mmx1200mm G2 Advanced Rack
- HPE 42U 600mmx1200mm G2 Advanced Rack
- HPE 42U 800mmx1200mm G2 Advanced Rack
- HPE 36U 600mmx1200mm G2 Advanced Rack
- HPE 36U 800mmx1200mm G2 Advanced Rack

Notes:

- For more information on the HPE rack offerings, please see the following URL: <https://www.hpe.com/info/rackandpower>
- For more information on PDUs, see: <http://www.hpe.com/servers/pdu>



Configuration Information

Step 8: Required power cords

HPE Alletra 6000 arrays and expansion shelves do not ship with any power cords by default and require a minimum of 4 power cords per system. Please ensure these are selected at time of quoting. Four power cords are required when connecting base arrays (C13/C14) or expansion shelves (C13/C14) to Rack-Mounted Power Distribution Units (PDU). Four country/region specific power cords are required when connecting base arrays or expansion shelves to standard office wall power outlets.

Description

Description	SKU
HPE PE361L - LS-60 250V 10Amp 1.8m IN FIO Power Cord	Q8G57A
HPE WS-016 - C13 250V 10Amp 2.5m ZA FIO Power Cord	Q8G58A
HPE SI-32 - C13 250V 10Amp 2.5m IL FIO Power Cord	Q8G59A
HPE CEI 23-16 - C13 250V 10Amp 2.5m IT FIO Power Cord	Q8G60A
HPE AS 3112 - C13 250V 10Amp 2.5m AU FIO Power Cord	Q8F89A
HPE WS-010A - C13 250V 10Amp 2.5m EU FIO Power Cord	Q8F90A
HPE BS 1363 UK10 - C13 250V 10Amp 2.5m UK FIO Power Cord	Q8F91A
HPE NEMA 5-15P - C13 125V 13Amp 1.8m US FIO Power Cord	Q8F92A
HPE GB2099 - C13 250V 10Amp 2.5m CN FIO Power Cord	Q8F93A
HPE WS-010A - C13 250V 10Amp 2.5m KR FIO Power Cord	Q8F94A
HPE JIS 8303 - C13 125V 12Amp 2.5m TW/JP FIO Power Cord	Q8F95A
HPE NEMA 6-15P - C13 250V 12Amp 2.5m JP FIO Power Cord	Q8F96A
HPE C13 - C14 250V 10Amp 2m WW PDU FIO Power Cord	R9D23A
HPE C13 - C14 250V 10Amp 2m IN PDU FIO Power Cord	R9D24A

Field Upgrade Options

The following product options are to upgrade currently installed Alletra 6000 All Flash Arrays.

Controller upgrades Max one of the following:						SKU
6010	6030	6050	6070	6090	SKU Description	SKU
Yes	No	No	No	No	HPE Alletra 6030 All Flash Array Dual Controller Field Upgrade	R6H91A
Yes	Yes	No	No	No	HPE Alletra 6050 All Flash Array Dual Controller Field Upgrade	R6H92A
Yes	Yes	Yes	No	No	HPE Alletra 6070 All Flash Array Dual Controller Field Upgrade	R6H93A
Yes	Yes	Yes	Yes	No	HPE Alletra 6090 All Flash Array Dual Controller Field Upgrade	R6H94A

SSD Capacity Upgrade on Head Max one of the following:						SKU
6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 23TB (12x1.92TB) NVMe Flash Carrier Flash Field Upgrade	R7S89A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 46TB (12x3.84TB) NVMe Flash Carrier Flash Field Upgrade	R7S90A
No	Yes	Yes	Yes	Yes	HPE Alletra 6000 92TB (12x7.68TB) NVMe Flash Carrier Flash Field Upgrade	R7S91A
No	No	Yes	Yes	Yes	HPE Alletra 6000 184TB (12x15.36TB) NVMe Flash Carrier Flash Field Upgrade	R7S92A

Head Network Add / Upgrade Options						SKU
6010	6030	6050	6070	6090	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10GbE 4-port Adapter Field Upgrade	Q8C68C
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10GBASE-T 4-port Adapter Field Upgrade	Q8C69C
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x32Gb 2-port Fibre Channel Adapter Field Upgrade	ROP41A

Configuration Information

6010	6030	6050	6070	6090	SKU Description	SKU
No	No	Yes	Yes	Yes	HPE Alletra 6000 1.5TB Storage Class Memory Adapter Field Upgrade	ROP48B
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x10/25GbE 2-port Adapter Field Upgrade	ROR13A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x32Gb 4-port Fibre Channel Adapter Field Upgrade	ROR15A
Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 2x100GbE 2-port Adapter Field Upgrade	ROR19A

Notes:

- Max One (1) Storage Class Memory kit (ROP46B or ROP48B) per 6050/6070/6090 array
- Max Two (2) 100GbE kits or 32Gb FC 4-port kits (ROR18A/ROR19A or ROR14A/ROR15A) per 6030/6050/6070/6090 array
- Max One (1) 100GbE kits or 32Gb FC 4-port kits (ROR18A/ROR19A or ROR14A/ROR15A) per 6010 array
- All 10GbE kits (Q8C17C and Q8C20C) and 32Gb FC kits (ROP34A and ROR14A) include transceivers
- The 10/25GbE Adapter Kit (ROR12A) and the 100GbE Adapter kit (ROR18A) do not include transceivers. If transceivers are required, they will need to be ordered separately.
- Each Head networking upgrade option includes two (2x) cards which are evenly populated in the two controllers.

Transceivers (FIO)	SKU Description	SKU
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x10Gb SFP+ SR FIO Transceiver	R7D05A
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x25Gb SFP28 SR 100m FIO Transceiver	R7D07A
Supported with 2x100GbE 2-port kits	HPE Alletra 6000 2x100Gb QSFP28 MPO SR4 100m FIO Transceiver	R7D08A
Transceivers (BTO)	SKU Description	SKU
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x10Gb SFP+ SR Transceiver	R7D09A
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x25Gb SFP28 SR 100m Transceiver	R7D11A
Supported with 2x100GbE 2-port kits	HPE Alletra 6000 2x100Gb QSFP28 MPO SR4 100m Transceiver	R7D12A
DAC Cables (BTO)	SKU Description	SKU
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x10Gb SFP+ to SFP+ 3m Direct Attach Copper Cable	R7D16A
Supported with 2x10/25GbE 2-port kits	HPE Alletra 6000 2x25Gb SFP28 to SFP28 3m Direct Attach Copper Cable	R7D17A
Supported with 2x100GbE 2-port kits	HPE Alletra 6000 2x100Gb QSFP28 to QSFP28 3m Direct Attach Copper Cable	R7D18A

6010	6030	6050	6070	6090	2140	SKU Description	SKU
Yes	Yes	Yes	Yes	Yes	Yes	HPE Alletra 6000 4x 1600W DC Power Supply Kit	R7G14A
No	Yes	Yes	Yes	Yes	No	HPE Alletra 6000 4x 1600W AC Power Supply Kit	R8U90A
Yes	No	No	No	No	Yes	HPE Alletra 6000 800W Titanium Spare Power Supply	SOR24A
No	Yes	Yes	Yes	Yes	No	HPE Alletra 6000 2200W Titanium Spare Power Supply	SOR25A
Yes	Yes	Yes	Yes	Yes	N/A	HPE Alletra 6000 2x100GbE 2-port OCP Mezzanine Adapter Field Upgrade	R6J22A

Notes:

- The AC and DC power supply kits listed are available as standalone only (BTO) and are not available for factory integration
- The DC Power Supply Kit (R7G14A) includes four (4) DC power supplies; one (1) DC Power Supply Kit per array or shelf should be ordered for systems to be installed in environments utilizing DC power infrastructure
- The 1600W AC power supplies (R8U90A) are 80 PLUS Platinum certified
- the SOR24A and the SOR25A AC power supplies are 80 PLUS Titanium certified



Technical Specifications

Physical Dimensions						
	Width in/mm	Depth in/mm	Height in/mm/U	Weight lb/kg		
HPE Alletra 6000	17.3/439	31.5/800	6.9/175.8/4	120/54.5		
Power Requirements						
	6010	6030	6050	6070	6090	2140
Input Voltage, frequency (R7G12A - 800W AC PSU w/C14 connector)	100-120V, 50-60Hz, 9.4A 200-240V, 50-60Hz, 4.5A			N/A	100-120V, 50-60Hz, 9.4A 200-240V, 50-60Hz, 4.5A	
Input Voltage, frequency (SOR22A - 800W AC PSU w/C14 connector)	200-240V, 50-60Hz, 4.35A	N/A			200-240V, 50-60Hz, 4.35A	
Input Voltage, frequency (R7G13A - 1600W AC PSU w/C14 connector)	N/A	200-240V, 50-60Hz, 8.7A			N/A	
Input Voltage, frequency (SOR23A - 2200W AC PSU w/C14 connector)	N/A	200-240V, 50-60Hz, 10 A			N/A	
Input Voltage, frequency (1600W DC PSU)	-48 to -72 VDC, 45A					
Max power requirements (VA)	1272	1697	1998	2443	2692	500
Thermal (BTU/hour)	3815	5043	6033	7022	7841	1711
Refrigeration (tons)	0.32	0.42	0.50	0.59	0.65	0.14

Notes:

- 6070 & 6090 require 1600W/2200W PSUs and 200-240V power or DC PSU
- For the highest redundancy, use 1600W/2200W PSUs with 6030 and 6050. The R7G12A power supplies support both low-line and high-line
- The R7G13A, SOR22A, SOR23A power supplies support high-line; no low-line support
- The R7G13A power supplies are recommended when there is a choice between R7G12A and R7G13A
- Both the R7G12A and the R7G13A AC power supplies are 80 PLUS Platinum certified
- Both the SOR22A and the SOR23A AC power supplies are 80 PLUS Titanium certified
- The Titanium certified power supply kits (SOR22A & SOR23A) are mandatory to meet EU Lot9 requirements

Environmental Specifications ¹	
Operating Temperature	10 - 35° C (50 - 95° F) Reduce rating by 1° F for each 1000 ft altitude (1.8° C/1,000 m)
Shipping Temperature	0° C - 40° C (32° F - 104° F) Maximum rate of change is 20°C/hr (36°F/hr)
Operating Altitude (ft/m) max.	10,000 ft / 3,048 m
Shipping Altitude (ft/m) max.	40,000ft/ 12,192 m
Humidity	8 - 90%, non-condensing
Shipping Humidity	5 - 95%, non-condensing
Operating Vibration	0.25 G, Sine 5 - 200 Hz (approx. 15 min/axis); 0.4 GRMS, Random 5 - 200 Hz (approx. 60 min/axis)
Non-operating Vibration	0.5 G, Sine 5 - 200 Hz (approx. 15 min/axis); 0.98 GRMS, Random 5 - 500Hz (approximate 30 min/axis)
Operating Shock	20 G, 2.5ms, half-sine, one shock on each side
Non-operating Shock	20 G, 10ms, square wave, one shock on each side

Notes: ¹ Specifications are subject to change without notice.

Technical Specifications

Electromagnetic Compatibility

- Subpart B of Part 15 of FCC Rules for Class A digital devices
- ICES-003, Issue 6, dated January 2016 (Class A)
- VCCI V-3: April 2014 (Class A)
- EN 55022:2010
- CISPR 22:2008
- AS/NZS CISPR 22:2009 +A1:2010
- EN55032:2012
- CISPR 32:2012
- EN 55024:2010
- CISPR 24:2010 +A1:2015
- TCVN 7189:2009
- NBTC TS 3001-2555
- TP TC 020/2011

Safety

- EN60950-1:2005 (Second Edition); Am1:2009 + Am2:2013
- IEC 60950-1:2005 (Second Edition); Am1:2009 + Am2:2013
- EN60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013
- UL/IEC 60960-1 2nd Ed. Am1 + Am2
- CNS14336-1 ('99)
- CNS13438 ('95)
- NOM-019-SCFI-1998
- NBTC TS 4001-2550
- TP TC 004/2011
- IS 13252 (PART 1):2010 +A1:2013 + A2:2-15
- SANS IEC 60950-1

Certifications / Markings

- UL
- cUL
- CE
- FCC Class A
- IC Class A
- VCCI Class A
- RCM
- BSMI Class A
- KC
- CCC Exemption
- NOM
- MoEc
- NBTC SDoC
- CITC/CoC*
- EAC
- BIS
- LOA (S. Africa)
- RoHS 2011/65/EU, EN50581:2012
- WEEE




Summary of Changes

Date	Version History	Action	Description of Change
18-Sep-2023	Version 15	Changed	Configuration Information section was updated
21-Aug-2023	Version 14	Changed	Service and Support and Configuration Information sections were updated
07-Aug-2023	Version 13	Changed	Overview, Configuration Information and Technical Specifications sections were updated
15-May-2023	Version 12	Changed	Configuration Information section was updated
06-Mar-2023	Version 11	Changed	Service and Support and Configuration Information sections were updated
06-Feb-2023	Version 10	Changed	Overview and Configuration Information sections were updated
10-Jan-2023	Version 9	Changed	Configuration Information section was updated
06-Jun-2022	Version 8	Changed	Standard Features, Service and Support and Configuration Information sections were updated.
07-Feb-2022	Version 7	Changed	Configuration Information section was updated.
06-Dec-2021	Version 6	Changed	Service and Support and Configuration Information sections were updated.
01-Nov-2021	Version 5	Changed	Configuration Information section was updated.
15-Sep-2021	Version 4	Changed	Standard Feature, Service and Support and Configuration Information sections were updated.
06-Jul-2021	Version 3	Changed	Overview, Service and Support and Configuration Information sections were updated.
17-May-2021	Version 2	Changed	Overview, Standard Features, Service and Support and Configuration Information sections were updated.
04-May-2021	Version 1	New	New QuickSpecs.



Copyright

**Make the right purchase decision.
Contact our presales specialists.**



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a50002567enw - 16722 - Worldwide - V15 - 18-September-2023